PLACID
PLACID INSTRUMENTS



PLACID
MEASUREMENT
MICROPHONE

PNP
22

ACCURATE & STABLE

PLACID MEASUREMENT MICROPHONES

Discover a wide selections of our measurement microphones according to your sound measurement needs

Placid Instruments BV
Newtonlaan 115
Office No. 2.21
3584 BH UTRECHT
THE NETHERLANDS
info@placidinstruments.com
www.placidinstruments.com

ASK US!
HERE

PLACID
PLACID INSTRUMENTS

NEW CALIBRATED INSTRUMENTS FOR REGISTERING NOISE AND VIBRATION



PLACID INSTRUMENTS BV
Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS
Phone +31 302106021
email info@placidinstruments.com
website www.placidinstruments.com

PLACID PNP22

1/2" STANDARD PREAMPLIFIER



Specification

Frequency Range
5.0 Hz to 100 kHz

Noise
< 2.0 µV

Usage
General purpose

The PLACID PNP22 ½" Preamplifier is a robust preamplifier designed to be used for acoustic measurements with condenser microphones. The self-noise is very low, it has a wide dynamic range and frequency response.

PLACID
PLACID INSTRUMENTS

NEW CALIBRATED INSTRUMENTS FOR REGISTERING NOISE AND VIBRATION



PLACID INSTRUMENTS BV
Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS
Phone +31 302106021
email info@placidinstruments.com
website www.placidinstruments.com

Specification

Design

All PLACID ICCP microphone preamplifiers are designed for ¼", ½" and 1" condenser microphones.
The preamplifiers are optimized to have a flat frequency response which will ensure high quality acoustic measurements.

Self Noise

The electrical circuit has especially been designed to ensure a low self-noise level which typically be much lower than the self-noise of the microphone cartridge.

Impedance

The PLACID PNP22 input impedance is over 5 Ω, the output impedance is less than 110 Ω .

Daily usage

- General-purpose preamplifier
- High-frequency measurements
- High-pressure measurements

PLACID
PLACID INSTRUMENTS

NEW CALIBRATED INSTRUMENTS FOR REGISTERING NOISE AND VIBRATION



PLACID INSTRUMENTS BV
Newtonlaan 115 Office No. 2.21 3584 BH UTRECHT, THE NETHERLANDS
Phone +31 302106021
email info@placidinstruments.com
website www.placidinstruments.com

DATASHEET PLACID PNP22

Frequency Response (Ref. 250 Hz, 0.2 dB)	Hz	5.0 to 100 kHz
Slew Rate	V/µs	3.5
Input Impedance	G Ω	➢ 5
Output Impedance	Ω	< 110
Max Output Voltage	Vrms	8.0
Noise (A-Weighted)	µV	< 2.0
Noise (Linear 20 Hz – 20 kHz)	µV	< 6.0
Gain	dB	- 0.15
DC – offset, minimum	V	15
DC- offset, maximum	V	24
Power Requirement	mA	ICP 2 to 20
Temperature operational range	Celcius	- 40 to 100
Temperature storage range	Celcius	-40 to 100
Humidity operational range noncondensing	% Rh	0 to 98
Output Connector Type		SMB
Diameter	Inch	½
Weight	Gram	14.5
Length	mm	35.0



PLACID

PLACID INSTRUMENTS

Placid Instruments BV

Newtonlaan 115, Office No. 2.21

3584 BH UTRECHT

THE NETHERLANDS

Phone landline : +31 302106021

Email : info@placidinstruments.com

www.placidinstruments.com

ASK US!
HERE